

BRIGHTSIGN XT

STATE-OF-THE-ART TECHNOLOGY AND DOLBY VISION™. ENTERPRISE PERFORMANCE.

BrightSign XT delivers unsurpassed performance for enterprise applications with a powerful 4K video engine, our fastest HTML and graphics engine and our most powerful CPU. This state-of-the-art technology for leading-edge digital signage installations supports H.264 & H.265 decoding, Dolby Vision and HDR10+** media profiles, Full HD and 4K playback including Mosaic Mode. It offers a hardware-accelerated HTML5 rendering engine that enables flawless playback of multiple modular HTML5 assets including Javascript, CSS animations, WebGL and even swipe/gesture interactivity. All XT models offer Gigabit Ethernet, and XT is the only product line offering 4K full resolution graphics, PoE+ as well as HDMI In for Live TV playback.











Standard I/O Player





Expanded I/O Player

Includes all the features BrightSign XT244, plus serial, dual USB (type A and C) and Live TV playback via the HDMI 2.0a input to play content from any broadcast channel – even protected HDCP content.



Features



Powerful 4K





BrightBeacon™







BrightSign App



H.265





dual decode

Remote Snapshot Sign Preview



Power over



BrightPlates^T



B-Deploy



IP Streaming Server







Digital Audio



Geo-Fencino

SSD M.2 SSD PCIe

^{**} HDR10+ functionality is planned to be released in 2019 on Series 4 players but is currently not available.

BrightSign®

SPECIFICATIONS

MODEL	XT244	XT1144
VIDEO ENGINE DECODER		
Native 4K@60p Dolby Vision and HDR10+ video decoding	Х	Х
Single video decoding: 4K or 1080p60	Χ	X
Dual video decoding: 4K or 1080p60	Х	Х
MEDIA FORMATS		
4K full resolution graphics	Х	Х
Video Codecs for 4K content: H.265/H.264	Χ	Х
Video Containers for 4K H.265 content: .ts, .mov, .mp4, .mkv	Х	Х
Video Codecs for Full HD: H.265, H.264 (MPEG-4 Part 10), MPEG-2	Х	Х
Video Containers for Full HD content: .ts, .mpg, .vob, .mov, .mp4, .m2ts	Х	Х
Image support up to 4K BMP, JPEG, PNG	Χ	X
Audio: MP2, MP3, AAC, and WAV (AC3 is passed through)	Χ	X
HTML5	X (Enterprise)	
DISPLAY RESOLUTIONS*		
4K resolutions: 4096x2160, 3840x2160, 3840x600	Χ	Х
Upscaling to: 3840x2160x24/25/29.97/30p	Χ	Χ
1920x1080, 1920x1200, 1600x1200, 1440x1050, 1440x900, 1360x768, 1280x1024, 1280x960, 1280x800, 1280x768, 1280x720, 1024x768, 800x600, 720x576, 720x480, 640x480	Х	Х
HARDWARE INTERFACES		
Locking Power Connector	Χ	Χ
External micro SD Slot (SDHC and SDXC); SDHC storage up to 32GB SDXC storage up to 2TB	Х	Χ
M.2 SSD PCIe Interface	Χ	Х
USB High Speed Host Port (also supports content updates)		X (2 ports: Type A&C)
12-pin Phoenix GPIO port with 8 bi-directional GPIOs	Χ	X
3.5mm RS-232 Serial Port		Х
3.5mm IR In/Out	Χ	X
3.5mm Audio Out (analog -or- SPDIF digital, non- simultaneous)	Х	Х
HDMI 2.0a Out	Χ	X
HDMI 2.0a Input	Х	
Ethernet	X (Giga	abit)
Power over Ethernet (PoE+)	X	Х
M.2 (E) Keyed Wi-Fi/Bluetooth Connector	Χ	Х
Wi-Fi External Antenna Connector	X	Х
Status LEDs	Power, Busy, W	ireless, Error
Reset Button	Х	Х
Real Time Clock	X	Х
FEATURES		
H.265 Decoding: smaller file sizes and higher quality content than H.264	Х	Х
Powerful 4K Video Engine: native 4K Dolby Vision and HDR10+ decoding, 4K upscaling, dual 4K video decoding and superior scaling technologies	Х	Х
Live TV: brings Live TV, even HDCP-protected content, to your signage via HDMI 2.0a Input		Χ

MODEL	XT244	XT1144
	X1244 X11144	
HTML5: hardware-accelerated HTML5 engine plays full screen and modular HTML5 assets up to 4K resolution layered together with high-bandwidth Full HD or 4K video	X (Enterprise)	
BrightBeacon™: 2-way Bluetooth/Beacon communication between mobile devices & signage (requires: wireless/ Bluetooth module)	Х	Х
BrightWall™: frame-accurate synchronized playback across multiple displays	X	Х
Autowall™: embraces the power of HTML5 to create unique multimedia video walls	Х	Х
Zones: playback multiple content types on a single screen	X	Χ
Mosaic Mode: play a multitude of smaller resolution videos simultaneously that add up to the maximum video resolution of the player	Х	Х
IP Streaming: play streaming media	Χ	Х
IP Streaming Server: serve IP streams from local storage	Х	Х
Encoding Server: transcode or composite/encode IP streams	X	Χ
Interactivity: connect virtually any type of interactive device to a multitude of interactive ports	X (GPIO, IR, UDP)	X (GPIO, dual USB, serial, IR, UDP)
Live Feeds: Live Data, Live Text, MRSS, Twitter, Flickr, etc.	Χ	Х
Tagging: BrightSign Network users can assign media and player tags for highly targeted content distribution	X	Х
BrightSign App: update signs with an iOS device	X	Χ
Geo-Fencing: trigger playback based on location (requires USB dongle)		Х
Sign Preview: preview presentation playback in BrightAuthor	X	Х
Remote Snapshot: remotely view a snapshot image of the display's playback	Х	Х
BrightPlates™: easy template-based sign creation service	X	Χ
Networking: update, manage and schedule your signage	Х	Χ
B-deploy: A setup feature to deploy many players at once	Х	Х
Extended Thermal: Supports ambient temperatures between 0° & 70° C at 90% max relative humidity, non-condensing	Х	Х
SOFTWARE		
Free BrightAuthor Software	X	X
BrightSign Networking Options	X	X
ACCESSORIES		
USB Button Pads		Χ
Wireless/Bluetooth Module	Х	Χ
MicroSD Class 10 Cards (various capacities)	X	X
MISCELLANEOUS		
Dimensions (W x H x D)	179.9 x 21.9 x 204.2mm or 7.1 x 0.86 x 8 in	
Weight	20 oz	
Power	12V / 3A (36 Watts)	
Multi-Country Power & Regulatory Approvals	Х	Χ
Built-in Wall Mounting Brackets	Х	Х
1 year warranty, parts and labor	X	X